














CABLE TIES										
<p>ONE PIECE SELF-LOCKING CABLE TIE. NO METAL BARBS. WRAP TIE AROUND CABLE, SLIP TAIL THROUGH HEAD & PULL TIGHT. TIE LOCKS IN PLACE AUTOMATICALLY. SNIP OFF: EXCESS TAIL. CABLE TIE MEET UL 94V-2 FLAMMABILITY RATINGS. TEMPERATURE RATING:-40F TO 185F GENERAL PURPOSE NYLON 6/6 IS SUITABLE FOR USE IN MOST PRACTICAL APPLICATIONS AT A CONTINUOUS TEMPERATURE UP TO 150F. UV STABILIZED NYLON 6/6 IS USED IN CONTINUOUS OR EXTENDED EXPOSURE TO OUTDOOR USE. THE NYLON CABLE TIE IS A WEATHER RESISTANT GRADE, ENDURING ADDITIONAL ULTRA-VIOLET (UV) LIGHT. UV STABILIZED CABLE TIES ARE AVAILABLE ONLY IN BLACK. RoHS COMPLIANT</p>										
<p>4" MINIATURE 18LB WIDTH 2.41MM THICKNESS 1.06MM BUNDLE DIAMETER .875 </p>										
	25 PC 7063-PK 7063-0-PK 7063-1-PK 7063-2-34 7063-3-PK	100 PC 7063-C 7063-0-C 7063-1-C 7063-2-36 7063-3-C	1000 PC 7063-M 7063-0-M	NATURAL UV BLACK BLUE BROWN GREEN	MILITARY SPEC MS3367-4-9 MS3367-4-0 MS3367-4-6 MS3367-4-1 MS3367-4-5	25 PC 7063-4-PK 7063-5-PK 7063-7-PK 7063-8-34 7063-9-PK	100 PC 7063-4-C 7063-5-C 7063-7-C 7063-8-36 7063-9-C	ORANGE RED YELLOW GREY PURPLE	MILITARY SPEC MS3367-4-3 MS3367-4-2 MS3367-4-4 MS3367-4-8 MS3367-4-7	
<p>6" INTERMEDIATE 40LB WIDTH 3.55MM THICKNESS 1.24MM BUNDLE DIAMETER 1.437 </p>										
	25 PC 7065-PK 7065-0-PK 7065-1-PK 7065-2-PK 7065-3-PK	100 PC 7065-C 7065-0-C 7065-1-C 7065-2-C 7065-3-C	1000 PC 7065-M 7065-0-M	NATURAL UV BLACK BLUE BROWN GREEN	MILITARY SPEC MS3367-5-9 MS3367-5-0 MS3367-5-6 MS3367-5-1 MS3367-5-5	25 PC 7065-4-PK 7065-5-PK 7065-7-PK 7065-8-PK 7065-9-PK	100 PC 7065-4-C 7065-5-C 7065-7-C 7065-8-C 7065-9-C	ORANGE RED YELLOW GREY PURPLE	MILITARY SPEC MS3367-5-3 MS3367-5-2 MS3367-5-4 MS3367-5-8 MS3367-5-7	
<p>7.5" STANDARD 50LB WIDTH 4.57MM THICKNESS 1.32MM BUNDLE DIAMETER 1.875 </p>										
	25 PC 7066-PK 7066-0-PK 7066-1-PK 7066N1-PK 7066-2-PK 7066-3-PK 7066N3-PK	100 PC 7066-C 7066-0-C 7066-1-C 7066N1-C 7066-2-C 7066-3-C 7066N3-C	1000 PC 7066-M 7066-0-M 7066-1-M	NATURAL UV BLACK BLUE NEON BLUE BROWN GREEN NEON GREEN	MILITARY SPEC MS3367-1-9 MS3367-1-0 MS3367-1-6 MS3367-1-1 MS3367-1-5	25 PC 7066-4-PK 7066N4-PK 7066-5-PK 7066-7-PK 7066N7-PK 7066-8-PK 7066-9-PK 7066N9-PK	100 PC 7066-4-C 7066N4-C 7066-5-C 7066-7-C 7066N7-C 7066-8-C 7066-9-C 7066N9-C	ORANGE NEON ORANGE RED YELLOW NEON YEL GREY PURPLE NEON PINK	MILITARY SPEC MS3367-1-3 MS3367-1-2 MS3367-1-4 MS3367-1-8 MS3367-1-7	
<p>8" INTERMEDIATE 40LB WIDTH 3.55MM THICKNESS 1.24MM BUNDLE DIAMETER 2.375 </p>										
	25 PC 7066L-PK	100 PC 7066L-C	1000 PC 7066L-M	NATURAL	MILITARY SPEC MS3367-5-9	25 PC 7066L0-PK	100 PC 7066L0-C	1000 PC 7066L0-M	UV BLACK	MILITARY SPEC MS3367-5-0
<p>11" STANDARD 50LB WIDTH 4.57MM THICKNESS 1.32MM BUNDLE DIAMETER 3.062 </p>										
	25 PC 7067-PK 7067-0-PK 7067-1-PK 7067-2-PK 7067-3-PK	100 PC 7067-C 7067-0-C 7067-1-C 7067-2-C 7067-3-C	1000 PC 7067-M 7067-0-M	NATURAL UV BLACK BLUE BROWN GREEN	MILITARY SPEC MS3367-7-9 MS3367-7-0 MS3367-7-6 MS3367-7-1 MS3367-7-5	25 PC 7067-4-PK 7067-5-PK 7067-7-PK 7067-8-PK 7067-9-PK	100 PC 7067-4-C 7067-5-C 7067-7-C 7067-8-C 7067-9-C	ORANGE RED YELLOW GREY PURPLE	MILITARY SPEC MS3367-7-3 MS3367-7-2 MS3367-7-4 MS3367-7-8 MS3367-7-7	
<p>14" STANDARD 50LB WIDTH 4.52MM THICKNESS 1.32MM BUNDLE DIAMETER 4 </p>										
	25 PC 7068-PK 7068-0-PK 7068-1-PK 7068-2-34 7068-3-34	100 PC 7068-C 7068-0-C 7068-1-C 7068-2-36 7068-3-36	1000 PC 7068-M 7068-0-M	NATURAL UV BLACK BLUE BROWN GREEN	MILITARY SPEC MS3367-2-9 MS3367-2-0 MS3367-2-6 MS3367-2-1 MS3367-2-5	25 PC 7068-4-34 7068-5-PK 7068-7-PK 7068-8-34 7068-9-34	100 PC 7068-4-C 7068-5-C 7068-7-C 7068-8-36 7068N9-36	ORANGE RED YELLOW GREY PURPLE NEON PINK	MILITARY SPEC MS3367-2-3 MS3367-2-2 MS3367-2-4 MS3367-2-8 MS3367-2-7	
<p>STANDARD CABLE TIE ASSORTMENTS RoHS COMPLIANT</p>										
	20-CS NATURAL 400 PC 21-CS BLACK 400 PC 7160-PK NATURAL & BLACK 60 PC 7166-PK NATURAL 25 PC	200-4", 100-8", 100-11" 200-4", 100-8", 100-11" 10-4" NATURAL & BLACK, 10-6" NATURAL & BLACK 10-8" NATURAL & BLACK 8-4" NATURAL, 8-6" NATURAL, 9-8" NATURAL								



RELEASABLE NATURAL 50LB CABLE TIES

TEMPORARILY OR PERMANENT BUNDLING ALLOWS FOR QUICK ADDITION OR REMOVAL OF WIRES OR ITEMS STRAP FINGER RELEASE LATCH ALLOWS EASY ACCESS

	25 PC	100 PC	LENGTH		WIDTH		THICKNESS		BUNDLE	
	7092-PK	7092-C	INCH	MM	INCH	MM	INCH	MM	DIAMETER	
	7093-PK	7093-C	5.9	150.	.29	7.6	.050	1.27	1.37	
	7094-PK	7094-C	7.8	200.	.29	7.6	.053	1.34	1.96	
			11.8	300.	.29	7.6	.053	1.34	3.15	

CLAMP CABLE TIES

CLAMP TIE HAS TRIANGULAR SHAPED TABS EXTENDING BENEATH THE HEAD, ALLOWING FOR OPTIMAL SURFACE CONTACT & COMPLETE CIRCUMFRENENTIAL COMPRESSION TO 360 DEGREES RECOMMENDED FOR SOFT RUBBER HOSE APPLICATIONS INCLUDING FUEL, WATER & AIR VACUUM LINES. UL94 V2 OPERATING TEMP -40C TO 105C CONTINUOUS

NATURAL POLYAMIDE 6.6 (PA66)		LENGTH		TIE TENSILE		WIDTH		BUNDLE DIAMETER		UV BLACK POLYAMIDE 6.6 HEAT STABILIZED		
25 PC	100 PC	INCH	MM			INCH	MM			25 PC	100 PC	
7164-PK	7164-C	4	100	20 LB		.10	2.5	.5		7164-0-PK	7164-0-C	
7168-PK	7168-C	8	205	60 LB		.19	4.7	1.77		7168-0-PK	7168-0-C	

LOW PROFILE CABLE TIES

REDUCED HEAD HEIGHT COMPARED TO STANDARD HEAD DESIGNS INCREASED SAFETY, ELIMINATES SNAGS, CUTS & ABRASIONS TO CABLES, HOSES, PRODUCTS & USERS NO SHARP TAIL CUTOFFS REMAINING TAIL SLIPS BACK INTO HEAD OF TIE LEAVING NO EXPOSED SHARP EDGES QUICK & SAFE REMOVAL SIMPLY CUT & PRY TOP CROSSBAR TO RELEASE CABLE TIE, ELIMINATING DAMAGE TO WIRES, TUBING, ETC. FLEXIBLE HEAD DESIGN ALLOWS THE HEAD TO EASILY FLEX AROUND THE TOTAL CIRCUMFERENCE OF TUBING OR BUNDLED WIRES TAMPER PROOF PAWL LOCATED UNDER THE TIE'S HEAD, MAKES IT INACCESSIBLE WHEN BUNDLED EASY HANDLING FINGER GRIPS ON THE TAIL PROVIDES A NO SLIP GRIP DURING INSERTION & TENSIONING

NATURAL 50 LB		LENGTH		WIDTH		THICKNESS		BUNDLE	UV BLACK 50 LB		
25 PC	100 PC	INCH	MM	INCH	MM	INCH	MM	DIAMETER	25 PC	100 PC	
7176-PK	7176-C	7.5	190.5	.17	4.49	.053	1.34	1.75	7176-0-PK	7176-0-C	
7177-34	7177-36	11	288.2	.17	4.49	.053	1.34	3.06	7177-0-34	7177-0-36	
7179-34	7179-36	14	372.1	.17	4.49	.053	1.34	4.06	7179-0-34	7179-0-36	
NATURAL 120 LB									UV BLACK 120 LB		
7178-34	7178-36	16.	406.4	.30	7.62	.075	1.90	4.06	7178-0-34	7178-0-36	

METAL PAWL UV BLACK CABLE TIES

BUNDLED EASY UV STABILIZED TEMPERATURE -40C TO 85C MATERIAL NYLON 66 (PA66) UL94-2V FLAME

25 PC	100 PC	LENGTH		TIE TENSILE		WIDTH		THICKNESS		BUNDLE	
		INCH	MM			MM	INCH	MM	DIAMETER		
7253-34	7253-36	4		18 LB		2.5	.045	1.15	.87"		
7256-34	7256-36	7.50		50 LB		4.8	.051	1.30	1.93"		
7257-34	7257-36	11		50 LB		4.8	.051	1.30	3.09"		
7258-34	7258-36	14		50 LB		4.8	.051	1.30	4.05"		

HEAT STABILIZED 50LB BLACK CABLE TIES

100 PC	1000 PC	LENGTH		WIDTH		THICKNESS		BUNDLE	
		INCH	MM	INCH	MM	INCH	MM	DIAMETER	
7266-36	7266-39	7.5	192.	.180	4.57	.052	1.32	1.675	
7267-36	7267-39	11.2	285.	.180	4.57	.052	1.32	3.062	

PUSH MOUNT HEAT STABILIZED BLACK NYLON CABLE TIES

FIR TREE GRIPS TO INSIDE OF HOLE USED WITH METAL, WOOD, PASTIC OR CAST IRON

25 PC	100 PC	LENGTH	TIE TENSILE	WIDTH	THICKNESS	BUNDLE DIAMETER	
7250-34	7250-36	8.39"	50 LB	.19"	.05"	2"	




7.5" 40LB CHROME CABLE TIES												
		5 PC	25 PC	100 PC	WIDTH INCH	BUNDLE DIAMETER	SEE PAGE 60 FOR CHROME LOOM					
	SILVER	7186-34	7186-35	7186-36	3.6	57MM						
	BLUE	7186-1-34	7186-1-35	7186-1-36	3.6	57MM						
	RED	7186-5-34	7186-5-35	7186-5-36	3.6	57MM						
ECONOMY CABLE TIES ROHS COMPLIANT												
		NATURAL		LENGTH	WIDTH	BUNDLE	TIE TENSILE	BLACK				
	100 PC	1000 PC	INCH	MM	INCH	MM	DIAMETER	18	100 PC	1000 PC		
	7063K-36	7063K-39	4	100	.10	2.5	30MM	40	7063K0-36	7063K0-39		
	7065K-36	7065K-39	5.9	150	.13	3.2	38MM	50	7065K0-36	7065K0-39		
	7066K-36	7066K-39	7.9	200	.19	4.8	56MM	50	7066K0-36	7066K0-39		
	7067K-36	7067K-39	11.3	286	.19	4.8	72MM	50	7067K0-36	7067K0-39		
	7068K-36	7068K-39	14.5	368	.19	4.8	109MM	50	7068K0-36	7068K0-39		
	7068HDK-36	7068HDK-39	14.5	368	.30	7.6	109MM	120	7068HK0-36	7068HK0-39		
	7069K-36	7069K-39	27.6	368	.35	8.8	702MM	175	7069K0-36	7069K0-39		
	7150K-36	7150K-39	36.0	914	.35	8.8	702MM	175	7150K0-36	7150K0-39		
CABLE TIES HEAVY DUTY												
HEAVY DUTY 120LB		WIDTH 7.62MM		THICKNESS 1.93MM		*NOT CSA APPROVED		ROHS COMPLIANT				
		NATURAL			BUNDLE	UV BLACK						
	LENGTH	25 PC	100 PC	MILITARY SPEC	DIAMETER	25 PC	100 PC	MILITARY SPEC				
	8.7"	7066HD-PK	7066HD-C	MS3367-3-9	2.06	7066HD0-PK	7066HD0-C	MS3367-3-0				
	15"	7068HD-PK	7068HD-C		4.06	7068HD0-PK	7068HD0-C					
28.5"	7070-PK*	7070-C*		8.	7070-0-PK*	7070-0-C*						
EXTRA HEAVY DUTY 175LB		WIDTH 8.63MM		THICKNESS 2.28MM		ROHS COMPLIANT						
		NATURAL			BUNDLE	UV BLACK						
	LENGTH	25 PC	100 PC	MILITARY SPEC	DIAMETER	25 PC	100 PC	MILITARY SPEC				
	25.2"	7069-PK	7069-C	MS3367-10-9	7.18	7069-0-PK	7069-0-C	MS3367-10-0				
	37.2"	7150HD-PK	7150HD-C	MS3367-13-9	11.00	7150HD0-PK	7150HD0-C	MS3367-13-0				
48.5"	7152HD-PK	7152HD-C	MS3367-16-9	14.50	7152HD0-PK	7152HD0-C	MS3367-16-0					
EXTRA HEAVY DUTY 250LB								ROHS COMPLIANT				
		NATURAL		WIDTH	BUNDLE	UV BLACK						
	LENGTH	25 PC	100 PC		DIAMETER	LENGTH	25 PC	100 PC				
	9"	7140HD-PK	7140HD-C	12.5MM	.55	20"	7141HD0PK	7141HD0-C				
				12.5MM	145							
MOUNTING TAB CABLE TIES												
CABLE TIE MEET UL 94V-2 FLAMMABILITY RATINGS. TEMPERATURE RATING:-40F TO 185F GENERAL PURPOSE NYLON 6/6 IS SUITABLE FOR USE IN MOST PRACTICAL APPLICATIONS AT A CONTINUOUS TEMPERATURE UP TO 150F. UV STABILIZED NYLON 6/6 IS USED IN CONTINUOUS OR EXTENDED EXPOSURE TO OUTDOOR USE.												
30LB #8 SCREW HOLE						ROHS COMPLIANT						
		NATURAL			WIDTH	THICKNESS	BUNDLE	UV BLACK				
	LENGTH	25 PC	100 PC	1000 PC	INCH	MM	INCH	MM	DIAMETER	25 PC	100 PC	1000 PC
	5.8"	7071-PK	7071-C	7071-M	.138	3.50	.045	1.14	1.25	7071-0-PK	7071-0-C	7071-0-39
50LB # 10 SCREW HOLE				WIDTH 4.49MM		ROHS COMPLIANT						
		NATURAL			THICKNESS	BUNDLE	UV BLACK					
	LENGTH	25 PC	100 PC	1000 PC	INCH	MM	DIAMETER	25 PC	100 PC	1000 PC		
	8"	7072-PK	7072-C	7072-M	.052	1.32	1.75	7072-0-PK	7072-0-C	7072-0-M		
	11.5"	7075-PK	7075-C	7075-M	.053	1.34	3.00	7075-0-PK	7075-0-C	7075-0-M		
	14.5"	7076-PK	7076-C	7076-M	.053	1.34	4.00	7076-0-PK	7076-0-C	7076-0-M		




ROHS COMPLIANT 15" ONLY **MOUNTING TAB CABLE TIES 120LB**

NATURAL		SCREW HOLE	WIDTH		THICKNESS		BUNDLE DIAMETER	LENGTH	UV BLACK	
25 PC	100 PC		INCH	MM	INCH	MM			25 PC	100 PC
7077-PK	7077-C	1/4"	.298	7.5	.075	1.9	4.06	15.7"	7077-0-PK	7077-0-C
7078-PK	7078-C	1/4"	.310	7.9	.083	2.1	6.00	22"	7078-0-PK	7078-0-C
7079-PK	7079-C	1/4"	.310	7.9	.083	2.1	8.00	29"		



ROHS COMPLIANT **ECONOMY MOUNTING TAB CABLE TIES**


NATURAL		SCREW HOLE	WIDTH		TIE TENSILE	BUNDLE DIAMETER	LENGTH	UV BLACK	
100 PC	1000 PC		INCH	MM	LBS.		INCH	100 PC	1000 PC
7071K-36	7071K-39	# 8	.14	3.6	40	35MM	5.9"	7071K0-36	7071K0-39
7072K-36	7072K-39	# 10	.14	3.6	50	50MM	8"	7072K0-36	7072K0-39
7075K-36	7075K-39	# 10	.19	4.8	50	75MM	11.8"	7075K0-36	7075K0-39
7076K-36	7076K-39	# 10	.19	4.8	50	109MM	14.5"	7076K0-36	7076K0-39
7077K-36	7077K-39	1/4"	.30	7.6	120	100MM	14.5"	7077K0-36	7077K0-39



ROHS COMPLIANT **MOUNTING PADS**

SAVES CABLE TIE CINCHING TIME PATENTED STAY-N-PLACE TAB KEEPS CABLE TIE HEAD FROM SLIDING DOWN BEHIND BUNDLE DURING VERTICAL APPLICATIONS & MAINTAINS PLACEMENT DURING HORIZONTAL APPLICATIONS EASY INSERTION OF CABLE TIES PATENTED LEAD-N-FEATURE FUNNELS CABLE TIES INTO POSITION & COUNTERSUNK SCREW HOLE ALLOWS CABLE TIE TO EASILY PASS OVER SCREW HEAD SAVES POSITIONING TIME WITH THE 4 SIDED ENTRY & CENTER SCREW HOLE UL/CSA APPROVED FOR INDOOR USE DESIGNED FOR USE WITH 50LB OR LIGHTER CABLE TIES

NATURAL		SCREW HOLE	LENGTH		HEIGHT		ADHESIVE	UV BLACK	
25 PC	100 PC		INCH	MM	INCH	MM		25 PC	100 PC
7082-PK	7082-C	#6	.74	18.7	.19	4.8	RUBBER	7082-0-34	7082-0-36
7080-PK	7080-C	#4	.99	25.1	.20	5.0	NONE	7080-0-34	7080-0-36
7081-PK	7081-C	#6	.99	25.1	.20	5.0	RUBBER	7081-0-34	7081-0-36
7085-34	7085-36	#6	.99	25.1	.20	5.0	ACRYLIC	7085-0-34	7085-0-36



ROHS COMPLIANT **SCREW MOUNTS**

SECURE SUPPORT DEEP CRADLE DESIGN PROVIDES MAXIMUM SUPPORT FOR LARGER BUNDLES & TUBING EASY INSERTION OF CABLE TIES DEEP RECESSED SCREW HOLE ALLOWS CABLE TIES TO PASS OVER SCREW HEAD

NATURAL		SCREW HOLE	LENGTH		HEIGHT		WIDTH		USE WITH CABLE TIE	BLACK	
25 PC	100 PC		INCH	MM	INCH	MM	INCH	MM		25 PC	100 PC
7084-34	7084-36	#6	.59	14.98	.27	6.8	.37	9.39	50 LB	7084-0-34	7084-0-36
7183-6-34	7183-6-36	#8	.60	15.4	.37	9.4	.60	15.4	50 LB	7183-0-34	7183-0-36
7083-34	7083-36	1/4"	.87	22.09	.38	9.6	.63	16.0	120 LB	7083-0-34	7083-0-36

